MCX
onstru

Reducing Greenhouse Gases in Capital Project Construction

Key Points

- The construction industry has a strategic role to play in the reduction of greenhouse gases (GHGs)
- The EPA Scope 1, 2, and 3 emissions to be reduced are described in the Executive Insight entitled, ^ v À] Œ } v u v š o U ^ }] o v ' } À Œ v v Z] • l •] v š Z v P] v Œ] v P v }
- Recommendations are made with respect to both the materials of construction as well as the various aspects of construction operations
- This Executive Insight focuses on net zero carbon as an industry goal

Introduction

The industry collectively accounts for 39 percent of global greenhouse gas emissions with construction (versus facility lifetime operations) accounting for 11 percent globally. If true greenhouse gas reduction is to be achieved, the construction industry will have to lead the way. The growing focus on ESG (environmental, social and governance) has put reducing greenhouse gases (GHGs) front and center. The construction industry is at the heart of this focus.

Reducing greenhouse gases associated with capital projects requires comprehensive life cycle analysis that addresses traditional economic drivers as well as the range of ESG considerations that are increasingly being called for. This begins with decisions on facility need, sizing, siting, and an expanded basis of design that addresses construction and operations and maintenance (O&M).

Two key factors stand out in consideration of the greenhouse gas component of environmental life cycle analysis: (1) the materials of construction and associated means and methods and (2) energy choices during construction and operations. As electricity use in construction increases, the electricity system must decarbonize significantly.

This Executive Insight focuses on the construction phase, recognizing that many decisions made during engineering will impact both construction and operations. Some strategic thoughts also are included to help guide industry actions as well as those of owners and constructors.

Greenhouse Gas Reduction during Construction

Greenhouse gas reduction during the construction phase is a supply chain challenge, not one readily met by a lone constructor. It also is a challenge that requires the industry, clients, and constructors to carefully consider targets and the KPIs (key performance indicators) that will lead to reducing GHGs. This last area on measurement and assignment of responsibility for reduction achievement is not a

Tactics to Consider

There are tactics the constructor may consider or adopt related to materials as well as construction operations. Effective adoption and implementation of many of these tactics will benefit from partnership with designers and owners. The following can serve as a checklist to assess individual company efforts.

Tactics to Materials Related

Cement/concrete

GHG abatement options:

- Identify where low-strength cement is sufficient
- Reduce cement clinker through use of supplementary cementitious materials (SCMs)
    - Slag, ash, pozzolan, calcined clays
- Evaluate cement clinker-free concrete (outside current standards)
- Optimize concrete recipes for specific location and design factors. This will lead to use of less cement as margins of design and construction are reduced to the essentials. Recipe improvements include admixtures, fillers, finer aggregates (reduced binder intensity)
-

- Reduce overspecification.
-

- Reduce haul distance through careful balancing of cuts and fills.

- Conduct regular maintenance of all plant equipment to sustain efficiencies and eliminate fugitive emissions from valves, seals, hoses, and gauges.
  - Proper maintenance of equipment, including lubrication and filter replacement or cleaning to improve fuel consumption
  - Consider remote monitoring and maintenance technologies
- Recover vent gases from tanks.

On-site construction

- Maximize use of more efficient/less wastage prefabrication, including use of precast concrete panels and beams (eliminates site-based formwork requirements; shifts construction into a more manufacturing-like facility)
- Reuse concrete elements at brownfield sites
- More broadly recycle concrete
- Consider non-steel options for traditional rebar uses.
- Reuse steel elements at brownfield sites.

Off-site construction

- Off-site construction and manufacturing to reduce waste from timber and concrete works.
- Reduces onsite energy usage by shifting production into a better controlled manufacturing-like environment

New Technologies and Materials

- Evaluate and prototype usage of new technologies.
  - 3D printing with various materials, including concrete, steel, and nylon reducing waste streams and associated carbon footprints.
  - Carbon Clean® reduces impact of CO_2 separation
  - Carbon Upcycling Technologies® captures CO_2 emissions to produce nanomaterials with greater reactivity and lower carbon footprint
  - Arqlite® technology to process unrecyclable plastic waste into artificial gravel for use in low CO_2 footprint
  - Hydrogen direct reduction of iron ore with hydrogen produced by renewable energy

- Evaluate new materials and products
  - Vertua® new net zero concrete
  - CarbiCrete® cement free, carbon negative concrete (typically block) made with industrial by-products, such as steel slag, and permanently captured carbon dioxide
  - BambooTECH® bambo

- Ferrock® compaction of variety of recycled materials, including silica from ground up glass and steel dust, into material with concrete-like properties but stronger. It traps carbon as part of drying process

Summary

The construction industry accounts for 39 percent of global greenhouse gas emissions with construction (versus facility lifetime operations) accounting for 11 percent globally. Greenhouse gas reduction requires the industry to lead the way. This Executive Insight focuses on the construction phase and is intended to provide insight into the strategies and tactics that E&C industry can adopt to meet this imperative.

References

1. Application of Life Cycle Analysis in the Capital Assets Industry; Construction Management Association of America (CMAA); ISBN-978-1-938014-06-2 (eBook); ISBN 978-1-938014-07-9 (print); June 2013.
2. Achieving Net-Zero Carbon Emissions in Construction Supply Chains—A Multidimensional Analysis of Residential Building Systems; Ida Karlsson, Johan Rootzén, Filip Johnsson, Martin Erlandsson; Developments in the Built Environment
3. Wyns, T., Axelson, M., 2016. The Final Frontier—De-Carbonising Energy-Intensive Industries, Inst. Eur. Stud. 64. https://doi.org/10.1017/CBO9781107415324.004
4. Embodied Carbon in Construction Calculator (EC3) Tool; https://docs.google.com/document/d/1S_SGqUta74y2I4nCMt_GPbkHErH4UofT/edit#

About the Author

Bob Prieto was elected to the National Academy of Construction in 2011. He is a senior executive who is effective in shaping and executing business strategy and a recognized leader within the infrastructure, engineering, and construction industries.

Although the author and NAC have made every effort to ensure accuracy and completeness of the advice or information presented within,